



C 70 TC Multi-functional system vehicle

Enormous traction and high efficiency make the C 70 TC implement carrier a powerful all-rounder in year-round use. Its 2-person cab increases the possible applications.







- High variability for vehicle types, construction and expansion options
- Flexible use and large selection of powerful implements.
- Two standard attachment areas (front/rear) and a 3rd attachment area for articulated implements.
- 2 Ergonomic and comfortable cab
- Optimal room climate in all weathers with air-conditioning, heating, and rotating air nozzles.
- 2-person cab with proper space for passenger.

3 Very easy servicing

- Hydraulically tiltable engine compartment cover allows tilting with articulated machine.
- Tanks can be swivelled out on both sides for easy cleaning and service access.

TECHNICAL DATA AND EQUIPMENT



C 70 TC Multi-functional system vehicle

Order no. 8.324-796.0 Wheelbase mm 1870 Permissible axle load, front kg 2300 Permissible axle load, rear kg 3500 Load kg max. 1511 Drive- performance kW / hp 48 / 67 Diesel particulate filter ■ Cylinder 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 x 1500 x 2300	Technical data		
Permissible axle load, front kg 2300 Permissible weight kg 3500 Load kg max. 1511 Drive- performance kW / hp 48 / 67 Diesel particulate filter ■ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300			8.324-796.0
Permissible axle load, rear kg 2300 Total permissible weight kg 3500 Load kg max. 1511 Drive- performance kW / hp 48 / 67 Diesel particulate filter ■ Cubic capacity cm³ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Wheelbase	mm	1870
Total permissible weight kg 3500 Load kg max. 1511 Drive- performance kW / hp 48 / 67 Diesel particulate filter ■ Cubic capacity cm³ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Permissible axle load, front	kg	2300
Load kg max. 1511 Drive- performance kW / hp 48 / 67 Diesel particulate filter I Cubic capacity cm³ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Permissible axle load, rear	kg	2300
Drive- performance kW / hp 48 / 67 Diesel particulate filter Image: Cubic capacity cm³ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Total permissible weight	kg	3500
Diesel particulate filter ■ Cubic capacity cm³ 2615 Cylinder 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Load	kg	max. 1511
Cubic capacity cm³ 2615 Cylinder 4 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Drive- performance	kW / hp	48 / 67
Cylinder 4 Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Diesel particulate filter		
Emissions standard STAGE V Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Cubic capacity	cm³	2615
Fuel tank I 65 max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Cylinder		4
max. Speed km/h 40 Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Emissions standard		STAGE V
Climbing ability % 100 Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	Fuel tank	1	65
Noise level (in cab) dB(A) 83 Dimensions (L x W x H) mm 4200 × 1500 × 2300	max. Speed	km/h	40
Dimensions (L x W x H) mm 4200 × 1500 × 2300	Climbing ability	%	100
	Noise level (in cab)	dB(A)	83
■ Included in the scope of supply.	Dimensions (L x W x H)	mm	4200 × 1500 × 2300
	■ Included in the scope of supply.		

Equipment	
Powerful traction drive	