




C 55 SC Multi-functional system vehicle

Versatility, efficiency and manoeuvrability make the C 55 SC implement carrier an all-rounder in year-round use. Always on board: High driving and working comfort.



1 High variability for vehicle types, construction and expansion options

- Flexible use and large selection of powerful implements.
- Two standard attachment areas (front/rear) and a 3rd attachment area for articulated implements.

2 Ergonomic and comfortable cab

- Optimal room climate in all weathers with air-conditioning, heating, and rotating air nozzles.
- 360° panoramic view for unobstructed view of working area and safe manoeuvring.

3 Very easy servicing

- Hydraulically tiltable engine compartment cover allows tilting with articulated machine.
- Tanks can be swivelled out on both sides for easy cleaning and service access.

C 55 SC Multi-functional system vehicle

Technical data

Order no.		8.331-171.0
Wheelbase	mm	1820
Permissible axle load, front	kg	2300
Permissible axle load, rear	kg	2300
Total permissible weight	kg	3500
Load	kg	max. 1572
Drive		Diesel
Motor manufacturer		Kubota
Drive- performance	kW / hp	42 / 57
Diesel particulate filter		■
Cubic capacity	cm ³	2615
Cylinder		4
Emissions standard		STAGE V
Fuel tank	l	65
max. Speed	km/h	40
Climbing ability	%	73
Noise level (in cab)	dB(A)	80
Dimensions (L x W x H)	mm	4000 × 1500 × 2300

■ Included in the scope of supply.