

**HOLDER
X SERIES**



X 45i

	1-person-cab
ENGINE	Kubota 4-cylinder petrol
Power	32.6 kW (44 HP)
Displacement	1605 cm ³
Rated speed	2600 rpm
Cooling system	Water cooling
Fuel tank capacity	42 l
DRIVE	Hydrostatic drive, stepless speed regulation, four equal sized wheels
Speed	0 – 27 km/h
Brakes	Hydraulic service brake on the front axle, active on all four wheels via the hydrostatic drive, mechanical parking brake on the front axle with two drum brakes
HYDRAULICS	First circuit 55 l/min at 2600 rpm, second circuit 30 l/min at 2600 rpm, third circuit 5 l/min at 2600 rpm
Quantity of hydraulic oil	19 l
Lifting force	Front 750 kg
WEIGHTS	Includes driver of 75 kg; depends on tyres and equipment
Empty weight	1280 kg
Permissible total weight	2300 kg
Permissible axle load	Front: 1190 kg / rear: 1190 kg
Tow bar load on the trailer coupling	75 kg
Towing capacity	Braked 900 kg
Maximum payload	1020 kg
DIMENSIONS	Tyres: 20 x 10.00-10
Wheelbase	1360 mm
Total length	2870 – 2905 mm
Total height	1960 mm
Total outer width	1094 mm (without external mirrors)
Turning circle	2150 mm
SUCTION SWEEPER	
Container gross / net	1 m ³ / 0.7 m ³
Fresh water tank	150 l
Max. sweeping width	2050 mm