KARCHER

HOLDER C 70 SC

Enormous traction and high efficiency make the C 70 SC implement carrier a powerful all-rounder in year-round use.



Order no.

8.324-795.0

Technical data		
Drive		Diesel
Traction drive		4-cylinder engine
Motor manufacturer		Kubota
Drive- performance	kW / hp	48 / 67
Cubic capacity	cm³	2615
Cylinder		4
Emissions standard		STAGE V
Fuel tank	I	65
max. Speed	km/h	40
Working speed	km/h	40
Permissible axle load, front	kg	2300
Permissible axle load, rear	kg	2300
Climbing ability	%	max. 100
Noise level (in cab)	dB(A)	80
Load	kg	max. 1872
Wheelbase	mm	1820
Diesel particulate filter		1
Total permissible weight	kg	3500
Weight without accessories	kg	2400
Dimensions (L × W × H)	mm	3831 × 1170 × 2020

Users must receive training on this device.

Equipment	
Particulate filter	
Air conditioning system	•
Heating	
Flashing lights	•
Year-round use	
Included in the scope of supply.	

Holder C 70 SC, 8.324-795.0, 2022-10-05

KARCHER





High variability for vehicle types, construction and expansion options

- Flexible use and large selection of powerful implements.
- Two standard attachment areas (front/rear) and a 3rd attachment area for articulated implements.
- Quick-change system enables 1 person to change implements without the need for any tools.

Spacious two-person comfort cab with optimal view of the work environment

- Optimal room climate in all weathers with air-conditioning, heating, and rotating air nozzles.
- 360° panoramic view for unobstructed view of working area and safe manoeuvring.
- Doors on both sides for safe entry and exit to side facing away from the road.



Short set-up and service times

- Hydraulically tiltable engine compartment cover allows tilting with articulated machine.
- Tanks can be swivelled out on both sides for easy cleaning and service access.