KARCHER

HOLDER C 70 TC

Enormous traction and high efficiency make the C 70 TC implement carrier a powerful all-rounder in year-round use. Its 2-person cab increases the possible applications.



Order no. 8.324-796.0

To the included		
Technical data		
Drive		Diesel
Traction drive		4-cylinder engine
Motor manufacturer		Kubota
Drive- performance	kW / hp	48 / 67
Cubic capacity	cm³	2615
Cylinder		4
Emissions standard		STAGE V
Fuel tank	1	65
max. Speed	km/h	40
Working speed	km/h	40
Permissible axle load, front	kg	2300
Permissible axle load, rear	kg	2300
Climbing ability	%	max. 100
Noise level (in cab)	dB(A)	83
Load	kg	max. 1711
Wheelbase	mm	1870
Diesel particulate filter		1
Total permissible weight	kg	3500
Weight without accessories	kg	2600
Dimensions (L × W × H)	mm	4192 × 1344 × 2230

Users must receive training on this device.

Equipment	
Particulate filter	
Air conditioning system	•
Heating	
Flashing lights	
Year-round use	•
Included in the scope of supply.	

KARCHER





High variability for vehicle types, construction and expansion options

- Flexible use and large selection of powerful implements.
- Two standard attachment areas (front/rear) and a 3rd attachment area for articulated implements.
- Quick-change system enables 1 person to change implements without the need for any tools.

Ergonomic and comfortable cab

- Optimal room climate in all weathers with air-conditioning, heating, and rotating air nozzles.
- 2-person cab with proper space for passenger.
- 360° panoramic view for unobstructed view of working area and safe manoeuvring.



Very easy servicing

- Hydraulically tiltable engine compartment cover allows tilting with articulated machine.
- Tanks can be swivelled out on both sides for easy cleaning and service access.