



# HOLDER

Kärcher Group

## ONE HOLDER. ENDLESS POSSIBILITIES.

### OUR SERVICES, YOUR BENEFITS:

- COMPREHENSIVE SERVICE NETWORK AND LOCAL PARTNERS
- RELIABLE SPARE PARTS SUPPLY
- PRACTICAL TRAINING
- VEHICLE PRESENTATIONS AND INSTRUCTIONS
- EXTENSIVE RENTAL FLEET FOR ALL-YEAR-ROUND USE



# FOUR SEASONS. ONE HOLDER. MULTIFUNCTION IS SO EASY.

A Holder represents all-year-round use under the hardest of conditions. These multifunctional implement carriers meet the highest demands and are tried and tested for operation and driving comfort, diversity, work efficiency, robustness and reliability. Together with perfectly matched attachments the vehicles provide a total package technically and economically outpacing standard solutions. See for yourself.

## WINTER MAINTENANCE



- SNOW PLOUGHING AND BLOWING
- SPREADERS AND LIQUID SALT SPRAYING
- SNOW SWEEPING
- SNOW LOADING
- CROSS-COUNTRY SKI-TRACKS
- ICE SCRAPING

## MOWING AND GROUND CARE



- MOWING
- MOWING-SUCTION COMBINATION
- MULCHING
- HEDGE CUTTING
- LAWN SWEEPING
- WATERING

## SWEEPING AND CLEANING



- SWEEPING-SUCTION COMBINATION
- SWEEPING
- LEAF REMOVAL
- WASHING
- SYNTHETIC TURF CLEANER
- WEED CONTROL

### OUR PRODUCTS STAND FOR:

+

+

+

+

#### QUALITY

- Robust, reliable and powerful
- Minimal downtime and high retention of value
- German premium manufacturer since 1888

#### VERSATILITY


- Vehicle programme from 44 to 129 HP
- Three attachment spaces and a broad attachment programme

#### MANOEUVRABILITY

- Articulated steering and four-wheel steering for the narrowest cornering and small turning circles
- Compact dimensions also for use in underground car parks and on pavements


#### COMFORT






- Well thought out and ergonomic operating concept
- High working and seating comfort
- Easy service access for maintenance and care



### EXPERIENCE HOLDER:

- Factory visit in Reutlingen
- At an individual live demonstration
- At exhibitions and roadshows
- On Facebook, YouTube and our Website



| HOLDER<br>PRODUCT RANGE<br>MUNICIPAL |  |  |  |  |  |
|--------------------------------------|---|---|---|---|---|
|                                      | X 45i   | B 55 SC / C 55 SC   | C 65 SC / C 70 SC   | S 100 / S 115 / S 130   | MUVO  |
| Cabin                                | 1-person cab  | 1-person cab  | 1-person cab*   | Combi cab   | 2-person cab  |
| Emission standard                    | Stage 5   | Stage 5   | Stage 5   | Stage 5   | EURO 6  |
| Power                                | 32.6 kW (44 HP)   | 42 kW (57 HP)   | 48 kW (65 HP)   | 74.4 kW (101 HP) /<br>85 kW (115 HP) /<br>95 kW (129 HP)                              | 80 kW (109 HP)  |
| Maxium speed                         | 27 km/h   | 40 km/h   | 40 km/h   | 40 km/h   | 60 km/h   |
| Tare weight                          | 1280 kg   | 1928–2445 kg  | 1928–2445 kg  | 3100–3450 kg  | 2790 kg   |
| Permissible total weight             | 2300 kg   | 3500 kg   | C 65: 3500–3800 kg<br>C 70: 3500–4000 kg  | 5500 kg /<br>optionally: 6000 kg  | 5500 kg   |
| Lifting capacity front / rare        | 750 kg / –  | 1100 kg / 1100 kg   | 1100 kg / 1100 kg   | 2700 kg / 2700 kg   | 1500 kg / –   |
| Hydraulic output                     | 1. circle 55 l/min / 2. circle<br>30 l/min / 3. circle 5 l/min                      | 35 l/min + 80 l/min   | 35 l/min + 70 l/min   | 25 l/min + 40 l/min +<br>120 l/min  | 115 l/min   |
| PTO shafts front / rare              | –   | B 55: – / hydraulically<br>C 55: opt. mech. / hydraul.                              | Optionally mechanically /<br>hydraulically  | Mechanically / –  | –   |
| Total outer width                    | 1094 mm   | 1170–1530 mm  | 1170–1530 mm  | 1360–1580 mm  | 1320–1687 mm  |
| Total height                         | 1960 mm   | 1985–2260 mm  | 2010–2260 mm  | 2233–2295 mm  | 2020–2060 mm  |
| Inside turning radius                | From 1710 mm  | From 1490 mm  | From 1490 mm  | From 1974 mm  | From 2330 mm  |

\* Also available with 2-person cab. Subject to technical changes. Correct use of the attachments according to the Holder Attachment Evaluation. Availability of vehicles and options depending on country.

Max Holder GmbH | Mahdenstraße 8 | 72768 Reutlingen | Germany | Phone: +49 7121 930729-0 | Fax: +49 7121 930729-213 | info@max-holder.com | www.max-holder.com