

**HOLDER  
MUVO**



**MUVO**

2-person-cab

**ENGINE**

VM 4-cylinder turbo diesel

**Emission standard**

EURO 6

**Power**

80 kW (109 HP)

**Displacement**

2970 cm<sup>3</sup>

**Torque**

420 Nm

**Cooling system**

Water cooling system

**Air filter**

Dry air filter with cyclone separator

**Diesel tank capacity**

65 l

**DRIVE**

Continuously variable hydrostatic drive/combination of 2-stage hydrostatic drive and mechanical 2-speed transmission

**All-wheel drive**

Permanent all-wheel drive

**Speed**

0 – 60 km/h

**Differential lock**

Can be applied to rear axle

**Brakes**

Two-circuit brake system with disc brakes on all four wheels

**Suspension**

Sprung front and rear axles with spring damper system

**HYDRAULICS**

Hydraulic pump with a delivery rate of up to 115 l/min  
Optional: Load sensing pump 115 l/min

**Quantity of hydraulic oil**

47 l

**Front attachment plate**

1500 kg lifting force

**Auxiliary control valves**

3 x double-acting front / 2 x double-acting rear / 1 x single-acting rear

**Climbing capacity**

Up to 55%

**CABIN**

Comfortable 2-person cab with full-sized second seat / 3-point seat belt / heated front windscreen / MP3 player and Bluetooth radio / heating / air conditioning

**Optional extras**

Air-suspended leather seat / comfortable seat / seat heating

**WEIGHTS**

Includes driver of 75 kg; depends on tyres and equipment

**Empty weight**

2790 kg (depending on equipment)

**Permissible total weight**

5500 kg

**Permissible axle load**

2800 kg

**Tow bar load on the trailer coupling**

150 kg

**Towing capacity**

Overrun braked 3500 kg

**Maximum payload**

2810 kg (depending on equipment)

**DIMENSIONS**

Depends on tyres

**Wheelbase**

2100 mm

**Total length**

3890 mm

**Total height**

2060 mm (with 245/75 R16)

**Total outer width**

1320 mm excl. mirrors (with 245/75 R16) / 1687 mm incl. mirrors

**Turning circle radius**

3650 mm

**Inner flatbed dimensions**

1810 x 1247 x 400 mm